

Amendments to and Listing of the Claims:

Please amend claims 1 and 4, so that the claims read as follows:

1. (Currently amended) An image forming apparatus, comprising:
an image bearing body that bears an electrostatic latent image formed thereon;
a developing unit that supplies a developer material to said image bearing body to develop the electrostatic latent image into a visible image;
a transfer unit that transfers the visible image onto a print medium;
a developer-removing blade in contact with said image bearing body to remove a residual amount of the developer material on said image bearing body;
wherein the developer material has substantially spherical particles and has a compressibility in the range of 30 to 55, the compressibility ~~in percentage~~ being given by
$$A=\{(D1-D2)/D1\} \times 100 \text{ } [[(\%)]]$$
where A is compressibility, D1 is aerated bulk density, and D2 is packed bulk density.
2. (Original) The image forming apparatus according to Claim 1, wherein said developer-removing blade has a longitudinally extending edge in contact with said image bearing body.
3. (Currently amended) The image forming apparatus according to Claim 1, wherein said developer-removing blade has a resilience in the range of 15 to 40% and is in contact with said image bearing body with ~~the~~ a line pressure in the range of 3 to 8 gf/mm.
4. (Currently amended) The image forming apparatus according to Claim 1, wherein said developer-removing blade has a ~~resiliency~~ resilience in the range of 20 to 35% and is in contact with said image bearing body with a line pressure in the range of 3 to 8 gf/mm.